



ANALOGUE CONSOLES

C2/C2S ultra compact



C2-2 2 MIC - 2 STEREO

- 2 mic input and 2 stereo input channels
- Comprehensive channel facilities including 2 band EQ and auxiliary
- Ultra compact lightweight design



C2S-2 2 MIC - 2 STEREO WITH USB

- 2 mic input and 2 stereo input channels
- Comprehensive channel facilities including 2 band EQ and auxiliary
- Ultra compact lightweight design
- Built in USB record / playback



C2-4 4 MIC - 2 STEREO

- 4 mic input and 2 stereo input channels
- Comprehensive channel facilities including 2 band EQ and auxiliary
- Ultra compact lightweight design



C2S-4 4 MIC - 2 STEREO WITH USB

- 4 mic input and 2 stereo input channels
- Comprehensive channel facilities including 2 band EQ and auxiliary
- Ultra compact lightweight design
- Built in USB record / playback



4 models - 2 or 4 mic input with/without USB interface **ultra compact design**
2-band EQ on all channels **USB interface for playback/record** **auxiliary output**
balanced inputs and outputs **multiple applications** **external power supply**

SPECIFICATIONS		C2-2	C2S-2	C2-4	C2S-4
Channels		6	6	8	8
Mic Inputs		2	2	4	4
Stereo Inputs		4	4	4	4
Frequency Response		20Hz-20kHz (+/-1dB)	20Hz-20kHz (+/-1dB)	20Hz-20kHz (+/-1dB)	20Hz-20kHz (+/-1dB)
Distortion		<0.08% @ -10dBu	<0.08% @ -10dBu	<0.08% @ -10dBu	<0.08% @ -10dBu
Residual Noise		<-98dB	<-98dB	<-98dB	<-98dB
Gain Range		0dB to +45dB	0dB to +45dB	0dB to +45dB	0dB to +45dB
Input Impedance	Mic Input	-20dB to +25dB	-20dB to +25dB	-20dB to +25dB	-20dB to +25dB
	Line Input	20k ohm balanced	20k ohm balanced	20k ohm balanced	20k ohm balanced
	Playback+ CDMP3	24k ohm unbalanced	24k ohm unbalanced	24k ohm unbalanced	24k ohm unbalanced
EQ	Hi	+/-15dB @ 12kHz	+/-15dB @ 12kHz	+/-15dB @ 12kHz	+/-15dB @ 12kHz
	Lo	+/-15dB @ 80Hz	+/-15dB @ 80Hz	+/-15dB @ 80Hz	+/-15dB @ 80Hz
Maximum Output	Main Mix	+21dB +/-2dB	+21dB +/-2dB	+21dB +/-2dB	+21dB +/-2dB
Output Impedance	Aux Send	+18dBu +/-2B	+18dBu +/-2B	+18dBu +/-2B	+18dBu +/-2B
	Record	1k ohm	1k ohm	1k ohm	1k ohm
	Headphones	25k ohm	25k ohm	25k ohm	25k ohm
USB		N/A	2 channel playback/record	N/A	2 channel playback/record
Dimensions (WxHxD)		165 x 75 x 244mm	165 x 75 x 244mm	218 x 75 x 244mm	218 x 75 x 244mm
Power Supply		Wall adaptor 100-240V ~ 50/60Hz	Wall adaptor 100-240V ~ 50/60Hz	Wall adaptor 100-240V ~ 50/60Hz	Wall adaptor 100-240V ~ 50/60Hz
Power Consumption		11W	11W	15W	15W