

TRX Series

Specification

The TRX series, with a choice of 16 models if you include the TRX218 double 18" subwoofer models are a great choice if you need reliability, affordability and simple good looks.

With impressive power ratings, active or passive models from 10" to 2 x 18" and virtually everything in between the TRX series will fit into any application.

Suitable for fixed installation, live PA, houses of worship or any other application where a powerful PA solution is required.

KEY Features

TWO **INPUTS WITH EQ** ON ACTIVES

1" THROAT COMPRESSION DRIVERS

DURABLE **MDF** CONSTRUCTION

MULTIPLE M10 FLYING POINTS

35MM TOP HAT FOR STAND MOUNT

CAST ALUMINIUM SPEAKER GRILLS

RECESSED **CARRY** HANDLES

REAR **CASTORS** ON TRX215 MODEL



AFFORDABLE PA SOLUTIONS

10"/12"/15",/2x15"
Full Range

15"/18"/2x18" Sub Bass
ACTIVE OR PASSIVE

Specification

	TRX-10A	TRX-12A	TRX-15A	TRX-15MA	TRX-215A	TRX-155A	TRX-185A
MAX SPL	124dB	126dB	126dB	127dB	132dB	128dB	129dB
PEAK	800W	1000W	1000W	1000W	2000W	2000W	2000W
PGM	400W	500W	500W	500W	1000W	1000W	1000W
RMS	200W	250W	250W	250W	500W	500W	500W
WEIGHT	20.8kg	25.5kg	31kg	24.7kg	54.7kg	47.6kg	57.8kg

Cabinet type	2-way active	2-way active	2-way active	2-way active	2-way active	Active subwoofer	Active subwoofer
Frequency response	60Hz-18kHz	50Hz-20kHz	45Hz-20kHz	45Hz-20kHz	45Hz-20kHz	35Hz-250Hz	38Hz-250Hz
Input sensitivity	-10dBv	-10dBv	-10dBv	-10dBv	-10dBv	-10dBu	-10dBu
Coverage (H x V)	80° x 60°	80° x 60°	80° x 60°	80° x 60°	80° x 60°	-	-
LF Driver	10"/50mm VC	12"/65mm VC	15"/65mm VC	15"/65mm VC	2 x 15"/65mm VC	15"/100mm VC	18"/75mm VC
HF Driver	1.35"/34mm VC	1.35"/34mm VC	1.35"/34mm VC	1.35"/34mm VC	1.75"/34mm VC	-	-
Crossover frequency	2kHz	2.2kHz	2kHz	2.2kHz	2.2kHz	80/100Hz	80/100Hz
Connection	2 x XLR/JACK input XLR output	2 x XLR/JACK input XLR output	2 x XLR/JACK input XLR output	2 x XLR/JACK input XLR output	2 x XLR/JACK input XLR output	XLR/JACK input XLR output	XLR/JACK input XLR output
Dimension (W x H x D)	354 x 555 x 426mm	409 x 628 x 472mm	453 x 710 x 518mm	429 x 635 x 484mm	472 x 1050 x 538mm	479 x 581 x 548mm	567 x 667 x 600mm

	TRX-10	TRX-12	TRX-15	TRX-15M	TRX-215	TRX-155	TRX-18S
MAX SPL	124dB	126dB	126dB	127dB	132dB	128dB	130dB
PEAK	600W	1000W	1000W	1000W	2000W	2400W	2400W
PGM	300W	500W	500W	500W	1000W	1200W	1200W
RMS	150W	250W	250W	250W	600W	600W	600W
WEIGHT	19kg	23kg	28.6kg	27kg	48kg	35.2kg	47.5kg

Cabinet type	2-way passive	2-way passive	2-way passive	2-way passive	2-way passive	passive subwoofer	passive subwoofer
Frequency response	60Hz-20kHz	50Hz-20kHz	45Hz-20kHz	45Hz-20kHz	45Hz-20kHz	40Hz-250Hz	38Hz-250Hz
Input sensitivity	94dB	96dB	96dB	97dB	99dB	96dB	96dB
Coverage (H x V)	80° x 60°	80° x 60°	80° x 60°	80° x 60°	80° x 60°	-	-
LF Driver	8 ohm	8 ohm	8 ohm	8 ohm	4 ohm	8 ohm	8 ohm
HF Driver	10"/50mm VC	12"/65mm VC	15"/65mm VC	15"/65mm VC	2 x 15"/65mm VC	15"/100mm VC	18"/100mm VC
Crossover frequency	1.35"/34mm VC	1.35"/34mm VC	1.35"/34mm VC	1.35"/34mm VC	1.75"/44mm VC	-	-
Connection	2kHz 2 x 4-pole	2.2kHz 2 x 4-pole	2kHz 2 x 4-pole	2.2kHz 2 x 4-pole	2.2kHz 2 x 4-pole	-	-
Dimension (W x H x D)	354 x 555 x 426mm	409 x 628 x 472mm	453 x 710 x 518mm	429 x 635 x 484mm	469 x 1050 x 538mm	479 x 581 x 548mm	567 x 667 x 600mm