mixBRIDGE/multiBRIDGE

UNIQUE HYBRID AUDIO INTERFACE AND MIXING CONSOLE

mixBRIDGE6 6 inputs (2mic/2stereo) with 2 track (stereo) USB recording

mixBRIDGE8 8 inputs (4mic/2stereo) with 2 track (stereo) USB recording

multiBRIDGE8 8 inputs (4mic/2stereo) with 8 track (multi) USB recording

Just a few reasons why we think it is great...

LIVE

Mix and record your live set, with up to 8 inputs (4 mic /2 stereo), enough for a small band, and even have a monitor mix.

REHEARSAL

Get a well mixed sound with the ability to easily record your rehearsals on your computer.

LIVESTREAM

Multiple inputs, a MIDI interface, twin headphone outputs and a space saving design that looks great on any desk.

PODCAST TRRS

(mix-minus) input for live phone call recording.

HOME RECORDING

High quality microphone pre-amps and up to 8 tracks of 24bit/96k USB output to work seamlessly with your DAW.





- 1 Professional MIC/LINE level inputs
- 2 Line level and instrument Hi-Z level inputs
- 3 2 band EQ, monitor bus and pan control
- 4 High power dual headphone output with independent levels
- 5 Space saving steel construction ideal for your desk or on the road
- 6 2 or 8 track USB send to DAW 2 track return from DAW

Rear Panel



- 1 USB audio/MIDI to/from your computer DAW 2 track (mixBRIDGE) / 8 track (multiBRIDGE)
- 2 Balanced outputs for monitoring or connecting to a PA system
- 3 AUX output for monitor mixes
- 4 TRRS AUX input with mix-minus, control live calls in podcasts or livestreams
- 5 Multiple input choices 2 x Stereo inputs
- 6 COMBO XLR / Jack inputs

Specification

	mixBRIDGE6	mixBRIDGE8	multiBRIDGE8
USB Output USB Input USB Sampling rate MIDI Interface	2 track (L-R) 2 track 24bit/48kHz n/a	2 track (L-R) 2 track 24bit/48kHz n/a	8 track (channels) 2 track 24bit/96kHz YES in/thru
MIC/LINE Inputs	$2 \times COMBO (2 \times mic / 1 \times line / 1 \times hi-z)$	4 x COMBO (4 x mic / 2	2 x line / 2 x hi-z)
Phantom Power Stereo Inputs Channel EQ AUX/PHONE Input MIX Output	+48V all mics individually switched 4 x 1/4" (6.35mm) jacks 2 band HI / LO 1 x 1/8" (3.5mm) TRRS (mix-minus) jack 2 x 1/4" (6.35mm) balanced jacks		
AUX/MONITOR Output	1 x 1/4" (6.35mm) mono jack		
MIC Gain LINE Gain MIC EIN Frequency response THD S/N Ratio Output Level EQ HI Frequency EQ LO Frequency Power Supply	+6dB to +50dB +10dB to -34dB <-100dB 10Hz - 20kHz +1/-3dB <=0.03% 80dB MAX +20dB (unbal/balanced) 12kHz (+/- 15dB) 80Hz (+/- 15dB 12V DC external PSU		
Dimensions (W x H x D) Net Weight	253 x 55 x 210mm 2.1kg	310 x 55 x 210mm 2.5kg	310 x 55 x210mm 2.5kg

